

中国认可 国际互认

检测 TESTING CNAS L7531

Date: 2020/05/19



Test Report

Report No.:2020119	0680	Page : 1/2			
Client: HANDAN Y	(IDAO METAL PRODUCTS CO., LTD				
Address: Deyuan Building No.183 Lianfang East Road,Handan,Hebei China					
Product:	High Strength Thread Bar 36 mm,Grade 930/1080Mpa+COUPLE	R 36(65×200)			
Dimension:	M36				
Quantity:	1PC				
Grade:					
Material:	PSB930				
Other description: PO NO.:PO NO-020010L0					
The information above is provided by the client. Our laboratory is not responsible for its authenticity.					
Sample Source:	Supplied by client				

Sample Source: Supplied by client Sample Description: Intercepting sect, plain. Receiving Date: 2020-05-11 Test Date: 2020-05-19

Specification & Conformance Requirement : The technical requirement supplied by client.

Test Result: See next page



Zhejiang Guojian Testing Technology Co.,Ltd.

Approved by :

characterg

Declaration: 1. This test report shall be invalid if without the laboratory testing seal or signatures of authorized signatory. 2. This test report shall be invalid if altered. 3. Our laboratory is only responsible for the original report. Copying, faxing, photocopying versions of the report is only for reference purpose. 4. This report is invalid if parted. 5. This test report shall not be reproduced except in full without the written approval of the laboratory. 6. This report is responsible for designated samples only. 7. Any objection of the test result should be declared timely. The tested samples will be kept for 45 days. 8. If tested samples are returned or expired, retest will no longer be offered. 9. The last digit of the report invalid, the changed information is identified in bold font. 10. If the uncertainty is not given in this report, the decision rule is sim


No.211, Yanbei Road, Haiyan, Zhejiang, China TEL:0573-86161256 86161587 FAX: 0573-86180133 Official website: http://www.chinazbj.com



JL3305-2018/2

Test Report

Report No.: 2020119680	Page : 2/2			
Test Item	Test Method	Requirement	Resul t	Conclusion
Tensile strength R _m /MPa	GB/T 228.1-2010	> 1080	1164, the fracture occur in the steel bar	Pass
		Re	viewed by: \mathcal{T}_{a}	ang Haizhong
001 001 001		老礼道 (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)		
헤				
差 重 0				
9 <u>5</u> 8				



---- REPORT FINALIZED -----